

### Product Features

- **Yttrium-fortified** cathode for ultra-resilience against accelerated degradation & fade.
- **Fully rechargeable** in as little as 2 hours.
- **Serial communication (CANBUS)** compatible with leading peripherals incl. Victron®, Studer®, Ingeteam®, SMA® & Goodwe®
- **On-board monitoring** & diagnostics via integrated user interface / display.
- **Marine-grade** stainless steel enclosure.
- **10 Year** product warranty.



### Technical Specifications

GENERAL INFORMATION	
Battery Type	LiFeYPO4 (Lithium Iron Yttrium Phosphate)
Usable Capacity	4000 Wh @C10, 25°C   3120 Wh @C2, 25°C
Nominal Voltage	13 VDC
Operating Voltage Range	11.6 VDC – 14.1 VDC
Operating Temperature Range	-20°C ~ 65°C
Cycle Life @ 100% DoD	> 3600 cycles (4000 Wh @C10, 25°C)
Cycle Life @ 80% DoD	> 5000 cycles (3200 Wh @C10, 25°C)
Cycle Life @ 70% DoD	> 7000 cycles (2800 Wh @C10, 25°C)
Dimensions (mm)	680 x 370 x 300mm (W x D x H)
Weight (kg)	47 kg

CHARGE / DISCHARGE	
Bulk Voltage	14.1 VDC
Discharge Voltage (min.)	11.6 V
Charge Current (max.)	250 A continuous (for 10 minutes max.)
Discharge Current (max.)	250 A continuous (for 10 minutes max.) 300 A burst (for 1 minute max.) 750 A peak (for 2 seconds max.)
Charge Power (continuous)	Maximum: 2kW   Recommended: 1kW
Discharge Power (continuous)	Maximum: 2kW   Recommended: 400W
Self-discharge Rate	< 2% per month
Charge & Discharge Efficiency	96% @C2   98% @C10

PROTECTION	
Isolator	750 A
In-line Fuse	2 x 125 A
Over-current Protection	250 A
Over-voltage Cut-out	< 15.6 V (3.90 V on any cell)
Under-voltage Cut-out	> 11.4 V (2.85 V on any cell)