

Features

- **LiFePO₄ performance in highly applicable sizes**
 - Designed for seamless replacement of existing 12V 7Ah lead acid batteries in most applications.
- **Ultra-efficient recharge capability**
 - Absorbs >96% of total charge energy supplied (max. 4% lost) every time, even at C1 rates.
 - Resilient against erratic charge & immune to associated lead acid vulnerabilities such as sulfation-induced capacity degradation.
- **Compatible with more than just 12V systems**
 - Up to 4 x batteries can be connected in series for installation in compatible 48V systems.
- **3 year product warranty.**



Technical Specifications

GENERAL SPECIFICATIONS

Battery chemistry	Lithium Iron Phosphate (LiFePO ₄)
Nominal voltage	13VDC
Usable capacity	104Wh @C10, 25°C
Operating voltage range	11.6V ~ 14.2V
Operating temperature range	Charge: 0°C ~ 45°C Discharge: -20°C ~ 65°C
Cycle life @100% DoD, C10, 25°C	> 2000 cycles (104Wh)
Cycle life @80% DoD, C10, 25°C	> 3000 cycles (83Wh)
Cycle life @50% DoD, C10, 25°C	> 5000 cycles (52Wh)
Dimensions	150 x 65 x 95mm (W x D x H)
Net weight (unboxed)	1.3kg
Warranty period	3 years

VOLTAGE & CURRENT

Bulk voltage (max. operating voltage)	14.2V
Float voltage (continuous charge voltage)	13.9V
Low voltage (min. operating voltage)	11.6V
Charge current	7.2A max. (C1)
Discharge current	1.44A continuous (C5) 7.2A peak (for max. 30 seconds)
Self-discharge rate	< 3% per month
Charge & discharge efficiency	96 ~ 99% @C1

SAFETY FEATURES

Ingress protection rating	IP56
Current over-charge protection range	24A ~ 36A
Voltage over-charge protection	< 15.6V (auto cut-off at first V _{cell} ≥ 3.9V)
Voltage over-discharge protection	> 10V (auto cut-off at first V _{cell} ≤ 2.5V)