

### Features

- **Premium quality LiFePO<sub>4</sub> technology**
  - Built with A-grade cells & integrated smart battery management system.
- **Stackable modular design**
  - Designed for seamless expansion of capacity in increments of 14.5kWh.
- **Operational lifespan of 10 years**
  - Guaranteed to retain >80% of original capacity at end-of-life (at 1 cycle/day).
- **Serial / CAN compatible** with leading inverters & other relevant peripherals.
- **10 year product warranty.**



### Technical Specifications

#### GENERAL SPECIFICATIONS

Battery chemistry	Lithium Iron Phosphate (LiFePO <sub>4</sub> )
Nominal voltage	52VDC
Usable capacity	14 560Wh @C2, 25°C
Operating voltage range	48V ~ 55.2V
Operating temperature range	Charge: 0°C ~ 50°C   Discharge: -10°C ~ 50°C
Cycle life @100% DoD, C2, 25°C	>3600 cycles (<20% fade)   7000 cycles (<40% fade)
Cycle life @ 80% DoD, C2, 25°C	>5000 cycles (<20% fade)   9000 cycles (<40% fade)
Cycle life @70% DoD, C2, 25°C	>7000 cycles (<20% fade)   12000 cycles (<40% fade)
Dimensions	370 x 262 x 870mm (W x H x D) incl. mounting extrusions.
Net weight (unboxed)	±104kg

#### VOLTAGE & CURRENT

Bulk voltage (operational max.)	55.2V
Low voltage (min).	48V
Charge current (max.)	240A continuous
Discharge current (max.)	240A continuous   300A burst (for < 1 minute)   750A peak (for < 2 seconds)
Charge power (max.)	Maximum: 7 280W (C2)   Recommended: 3 640W (C4)
Discharge power	Maximum: 7 280W (C2)   Recommended: 1 248W (C10)
Self-discharge rate	< 2% per month
Charge/discharge efficiency	96% @C2   98% @C10

#### SAFETY FEATURES

Isolator	400A
Inline fuse	500A
Current over-charge protection	250A
Voltage over-charge protection	< 58.4V (auto cut-off at first V <sub>cell</sub> ≥ 3.65V)
Voltage over-discharge protection	> 45.6V (auto cut-off at first V <sub>cell</sub> ≤ 2.85V)