

Features

- **Ultra-resilient LiFePO₄ electrochemistry**
 - Built with premium quality LiFePO₄ cells for sustained day-to-day performance in high demand applications.
- **Exceptional charge & discharge efficiency**
 - Can be recharged from 0-100% SoC in just 2 hours.
- **Intelligent integrated electronic BMS featuring:**
 - Advanced active balancing technology.
 - Extensive autonomous protective measures.
 - Serial communication with a wide list of peripherals.
- **Inherently safe & user-friendly by design**
 - Modular layout for safer transportation & easy assembly.
- **10 year product warranty.**



Technical Specifications

GENERAL SPECIFICATIONS

Battery chemistry	Lithium Iron Phosphate (LiFePO ₄)
Nominal voltage	615VDC
Usable capacity	193 110Wh @C2, 25°C
Operating voltage range	537.6V ~ 691.2V
Cycle life @100% DoD, C2, 25°C	>3600 cycles / <20% fade @EoL >7000 cycles / <40% fade @EoL
Cycle life @80% DoD, C2, 25°C	>5000 cycles / <20% fade @EoL >9000 cycles / <40% fade @EoL
Cycle life @70% DoD, C2, 25°C	>7000 cycles / <20% fade @EoL >12000 cycles / <40% fade @EoL
Multi-unit configuration limit	Maximum 1S20P (±3.8MWh max. total capacity)
Dimensions	960 x 790 x 1865mm (W x D x H)
Net weight (unboxed)	±1090kg

VOLTAGE, CURRENT & POWER SPECIFICATIONS

Maximum (bulk) voltage	691.2V (3.6V per cell)
Minimum voltage	537.6V (2.8V per cell)
Max. charge current	Recommended (C2): 157A Peak: 200A
Max. discharge current	Recommended (C2): 157A Peak: 200A
Max. charge power @V _(nom)	Recommended (C2): 96 555W Peak: 123 000W
Max. discharge power @V _(nom)	Recommended (C2): 96 555W Peak: 123 000W
Charge efficiency	96% @C2, 25°C 98% @C10, 25°C
Self-discharge rate	<2% per month

ENVIRONMENTAL & SAFETY SPECIFICATIONS

Ambient temperature range	Operational: 5°C ~ 45°C Stored: (-20°C) ~ 45°C
Ambient humidity range	5 ~ 85% relative humidity (non-condensing)
Maximum altitude	2000m
Voltage over-charge protection	Auto-disconnect triggered upon any V _(module) ≥ 57.6V
Voltage over-discharge protection	Auto-disconnect triggered upon any V _(module) ≤ 44.8V
Current protection	16A > (Auto-disconnect triggered) > 200A
Inline fuse	1 x 450A